



Heavy duty forestry mulcher for tractors between 150 and 230 HP. Equipped with swinging hammers for the cleaning of brushwood, which favors the growth of trees, the reclamation of land, the maintenance and restoration of banks, the maintenance of areas under power lines, forestry roads, fire blocking lines. Equipped with rotor of fixed tooth with system FIXE TOP, for thick wood and stumps. This mulcher integrates all the necessary options for an optimal forest work.

CHARACTERISTICS

- Steel-plate chassis, thickness 10 mm.
- Rotor POLSER + of 625 mm. of diameter.
- Gearbox RAIL BOX with freewheel.
- 2 x 4 XPC side belt transmission.
- Swinging hammers or fixed tooth carbide.
- Supports of bearing rotor in steel.
- Oscillating bearings of double row of rollers.
- Double front safety chains.
- PTO 1.000 rpm.
- Steel counter hammers.
- Skid shoes adjustable.
- System antiwire in rotor.
- Internal reinforcements in chassis.
- Hydraulic rear hood.
- Compact drive cover.
- Hydraulic pushing frame.
- Pulleys of diameter 290 mm.
- Model built under EC Normative.
- Safety indicators visible to personnel.



Pushing frame
Hydraulic rear hood
System antiwire in rotor



| MODEL | mm | KW-HP | [Icon] | [Icon] | [Icon] | [Icon] | Nº BELTS TYPE | [Diagram] | | | | | | |
|--------|------|------------------------|--------|--------|--------|--------|---------------|-----------|------|------|------|------|------|------|
| | | | | | | | | A mm | A in | B mm | B in | C mm | C in | |
| T-2000 | 2000 | 110 - 150 147 - 200 | 20 | 48 | 26 | 2644 | 2 x 4 XPC | 2384 | 94" | 1550 | 61" | 1680 | 66" | 1000 |
| T-2300 | 2300 | 118 - 160 147 - 200 | 20 | 56 | 28 | 2859 | 2 x 4 XPC | 2690 | 106" | 1550 | 61" | 1680 | 66" | 1000 |
| T-2500 | 2500 | 132 - 180 169 - 230 | 25 | 60 | 30 | 3115 | 2 x 4 XPC | 2884 | 113" | 1550 | 61" | 1680 | 66" | 1000 |

FIXE TOP System



OPTIONS



- Torque converter

