



Heavy duty forestry mulcher for tractors between 120 and 230 HP. Suitable for the cleaning of brushwood, which favors the growth of trees, the reclamation of land, the maintenance and restoration of banks, the maintenance of areas under power lines, forestry roads, fire blocking lines, etc. Rotor of forest conception with swinging hammers of trapezoidal shape or fixed tooth carbide. The gearbox is put off with regard to the rotor to reduce the angulation of the transmission. It incorporates rotor POLSER+ of 550 mm of diameter. Hooking: fixed and movable.

CHARACTERISTICS

- Steel-plate chassis, thickness 10 mm.
- Rotor POLSER + of 550 mm. of diameter.
- Gearbox SERRAT with RAIL BOX System.
- 2 x 3 XPC side belt transmission.
- Swinging hammers or fixed tooth carbide.
- Supports of bearing rotor in steel.
- Oscillating bearings of double row of rollers.
- Front safety chains.
- PTO 1.000 rpm.
- Steel counter hammers.
- Skid shoes adjustable.
- System antiwire in rotor.
- Internal reinforcements in chassis.
- Hydraulic rear hood.
- Compact drive cover.
- Model built under EC Normative.
- Safety indicators visible to personnel.



MODEL	mm	KW-HP	16	48	26	1865	Nº BELTS TYPE	Diagram Dimensions						
								A mm	A in	B mm	B in	C mm	C in	
T-2000	2000	89 - 120 172 - 230	16	48	26	1865	2 x 3 XPC	2345	92"	1690	67"	1395	55"	1000
T-2300	2300	89 - 120 172 - 230	20	54	30	2065	2 x 3 XPC	2645	92"	1690	67"	1395	55"	1000
T-2500	2500	89 - 120 172 - 230	20	60	32	2265	2 x 3 XPC	2845	92"	1690	67"	1395	55"	1000

OPTIONS



• DRR



• FIXE TOP System

